







Key features

- Visible beans & ingredient canisters
- CoEx® brewer & 2 whole bean grinders
- 10.4" high res full color touch screen
- Keyless cleaning & operation
- Aluminum housing
- LED illuminated ingredient canisters
- Separate hot water outlet

Options

- Branding and/or customized colors
- On-screen communication options
- Connect.Me® [online monitoring]
- Base cabinet [with condiment trays]
- Increased capacities
- Waste guide & drain
- Table between base and machine



Nio 20.3 CoEx® bean2cup double bean



Dimensions		inch
Machine	h	23.6
	W	18.1
	d	21.3
Base Cabinet	h	33.5
	W	18.1
	d	21.3
Weight	77	lb

Specifications

MoVeC-ICEq® & USB upload

10,4" resolution: 800x600

User Interface: DJD/Nio

Connection for payment systems [MDB]

Multiple languages possible

Cup-sensors

Strength selections menus

Number selection

Boiler: 2x 0.4L


Pressure: max 12 Bar

Selections

Whole Bean Coffee I	Hot Chocolate
Espresso	Chocomilk
Double Espresso	Espresschoc
Whole Bean Coffee II	Cappuccino I
Espresso II	Cappuccino II
Double Espresso II	Cafe au Lait
Latte Macchiato	Cafe Latte
Customized recipes **	Sugar
Chilled (sparkling) water **	Hot water

^{**} optional, ask for details & conditions

Canisters




Capacities	#	lbs	Cups	
Whole Bean Coffee I	1	2.43	150	
Whole Bean Coffee II	2	2.43	150	
Chocolate	3	2.78	55	
Milktopping	4	1.79	160	
Vanilla	5	3.24	245	

Waste bucket [accessible from outside]

(number of cups may vary depending on settings)













Connections

- 100-120 Volt AC
- 50/60 Hz
- 1200 Watt
- 3/4" BSP [15 mm] mains
- waterfilter & waterlock recommended
- USB [outside access]
- LAN or 4G LTE







 ≥ 100